



FOTON



DEK MOTORS

Concessionnaire Officiel

Route de la plage EXT module k phase 4 N°A 39 BP: 1067, Nouakchott - Mauritanie
Tél. : +222 45 25 78 02 - +222 25 05 55 31 GSM : + 222 37 02 91 90, Fax +222 45 29 19 30,
Email: info@dekmotors.com site web: www.dekmotors.com

FICHE TECHNIQUE

Vehicle brand		FOTON OLLIN (1.5 T)
Vehicle model		BJ1039V3JD3-1
Cabin		L1695 Single row seat, Titable
Whole vehicle main dimensions	Overall dimensions (LxWxH)mm	4805×1720×2150
	Inner dimensions of the cargo body (LxWxH)mm	3070×1610×360
	Driving type	4x2
	Wheel base (mm)	2490
	Wheel track (front/rear) (mm)	1385/1395
	Min. ground clearance (mm)	181
Weight data	Curb weight (kg)	1870
	Rated payload (kg)	1500
	Persons in cab (persons)	2
	Gross vehicle weight (kg)	3500
Whole vehicle main performance	Max. speed (km/h)	95
	Max. slope of climb (%)	28
	Min. turning diameter (m)	10,6
Engine	Model	BJ493Q(Euro I)
	Type	Four-cylinder, in-line,water cooling, four-stroke ,diesel engine
	Displacement (L)	2,771
	Rated power (kw/rpm)	57/3600
	Max torque (N.m/rpm)	172/2200
Gearbox	Model	JC5-21
	Speed ratio	11:5.594 12:2.814 13:1.660 14:1.000 15:0.794 1R:5.334
Clutch	Type	Diaphragm spring clutch φ240×φ160
Rear axle	Type/Main reducer ratio	Whole banjo type,Speed ratio:5.125
Suspension	Front suspension/Leaf spring number	non-independent suspension, leaf spring : 5
	Rear suspension/Leaf spring number	non-independent suspension, leaf spring : 7
Steering gear	Type	Mechanical circular ball type
Brake system	Service brake and boostingType	hydraulic drum brake
	Parking brake	Central drum brake
	Auxiliary brake	/
Wheels and tyre size		4+1/6.50R15
Electric device	Rated voltage	12V
Fuel tank (L)		55
Basic equipment		tiltable、 Heater, Adjustable steering wheel、 electic flameout device
1039V3JD3-01ZA08		Basic equipment+A/C+power steering